AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1.   (currently amended) A transmitter assembly ~~including~~ comprising:

a pre-distortion type linearizer to cancel a distortion component caused in a transmission signal and a correction data component~~, comprising:~~; and

first storage means for preliminarily storing said correction data; component

wherein said first storage means manages said correction data component as a table per transmission level and

wherein said transmission level is a sum of an alternating current voltage value corresponding to an instantaneous power of a the transmission signal and a direct current voltage corresponding to a part of the power of ~~a~~ the a transmission output signal.

Claim 2 (canceled).

3.   (currently amended): ~~A~~ The transmitter assembly as set forth in claim 1, which further comprises:

second storage means having a plurality of tables of said correction data component per transmission frequency and environmental temperature; and

means for updating content of said first storage means with the corresponding table of

said second storage means when at least one of the transmission frequency and the

environmental temperature is varied.

4.   (currently amended): A distortion compensation method for a transmitter

~~including a pre-distortion type linearizer to cancel a distortion component caused in a~~

~~transmission signal and a correction data component,~~ comprising:

reading out a value corresponding to a transmission level from a first storage means

preliminarily storing ~~said~~ a correction data component; and

inputting the read out value to ~~said~~ a pre-distortion type linearizer;

wherein said first storage means manages said correction data component in a form of a

table per transmission level; and

wherein said transmission level is a sum of an alternating current voltage value

corresponding to an instantaneous power of a transmission signal and a direct current voltage

corresponding to a part of the power of transmission output signal.

Claim 5 (canceled).

6.   (currently amended): ~~A~~ The distortion compensation method as set forth in claim

4, wherein a storage content of said first storage means is updated with a corresponding table in

said second storage means storing a plurality of tables storing said correction data component per

3

transmission frequency and environmental temperature when at least one of said transmission

frequency and environmental temperature is varied.

7.   (currently amended) A-The transmitter assembly as set forth in claim 2̶1, wherein

an address corresponding to said transmission level and ȿ̶aȋd̶ correction data component

corresponding to said address are stored in said first storage means.

Claim 8 (canceled).

9.   (currently amended): A-The transmitter assembly as set forth in claim 1, wherein

said correction data component consists of a predetermined amplitude value and a predetermined

phase value of the transmission signal.

10.   (currently amended): A-The distortion compensation method as set forth in claim

5̶4, wherein tȟe̶ an address corresponding to the transmission level and the correction data

component corresponding to said address are stored in said first storage means.

Claim 11 (canceled).

4

12.   (currently amended): A-The distortion compensation method as set forth in claim

4, wherein said correction data component consists of a predetermined amplitude value and a

predetermined phase value of the transmission signal.

13.   (currently amended): A transmitter assembly including comprising:

a pre-distortion type linearizer to cancel a distortion component caused in a transmission

signal and a correction data component comprising:

transmission signal generating means generating a base-band baseband signal of an I

signal and a Q signal; and

transmission means modulating and amplifying said baseband base-band signal into an RF

signal; and

said pre-distortion type linearizer being provided between an output of said transmission

signal generating means and an input of said transmission means; and

directional coupling means dividing said RF signal; and

power detecting means detecting said RF signal and outputting a transmission level to

address generating means; and

power calculating means calculating an instantaneous power of said baseband base-band

signal to output to said address generating means; and

said address generating means detecting an address of data to be output by a first storage

means from said transmission level and said instantaneous power of said baseband base-band

signal; and

said first storage means for preliminarily storing said correction data component.

14.   (currently amended): A-The transmitter assembly as set forth in claim 13,

wherein said first storage means manages correction data as a table per said transmission level.

15.   (currently amended): A-The transmitter assembly as set forth in claim 13,

which further comprises:

second storage means having a plurality of tables of said correction data component per

transmission frequency and environmental temperature; and

means for updating content of said first storage means with the corresponding table of

said second storage means when at least one of the transmission frequency and the

environmental temperature is varied.

16.   (currently amended): A-The transmitter assembly as set forth in claim 14,

wherein an address corresponding to said transmission level and a correction data component

corresponding to said address are stored in said first storage means.

17.   (currently amended) A-The transmitter assembly as set forth in claim 14, wherein

said transmission level is a sum of an alternating current voltage value corresponding to an

instantaneous power of a transmission signal and a direct current voltage corresponding to a part

of the power of transmission output signal.

18.   (currently amended): ~~A~~ The transmitter assembly as set forth in claim 13,

wherein said correction data component consists of a predetermined amplitude value and a

predetermined phase value of the transmission signal.

19.   (currently amended): A distortion compensation method for a transmitter

~~including a pre-distortion type linearizer to cancel a distortion component caused in a~~

~~transmission signal and a correction data component,~~ comprising:

providing ~~said~~ a pre-distortion type linearizer between an output of ~~said~~ a transmission

signal generating means and an input of a transmission means; ~~and~~

dividing RF signal by directional coupling means; ~~and~~

detecting said RF signal and outputting a transmission level to address generating means

by power detecting means; ~~and~~

calculating an instantaneous power of a base band signal to output to said address

generating means by power calculating means; ~~and~~

determining an address of data to be output by a first storage means from said

transmission level and said instantaneous power of said base band signal, by said address

generating means reading out a value corresponding to ~~a~~ said transmission level from said first

storage means preliminarily storing ~~said~~ a correction data component; and

inputting the read out value to said pre-distortion type linearizer.

20.   (currently amended): A-The distortion compensation method as set forth in claim

19, wherein said first storage means manages the correction data component in a form of a table

per said transmission level.

21.   (currently amended): A-The distortion compensation method as set forth in claim

19, wherein a storage content of said first storage means is updated with a corresponding table in

said-a second storage means storing a plurality of tables storing said correction data component

per transmission frequency and environmental temperature when at least one of said transmission

frequency and environmental temperature is varied.

22.   (currently amended): A-The distortion compensation method as set forth in claim

20, wherein the address corresponding to the transmission level and the correction data

component corresponding to said address are stored in said first storage means.

23.   (currently amended): A-The distortion compensation method as set forth in claim

20, wherein said transmission level is a sum of an alternating current voltage value

corresponding to an instantaneous power of a-said transmission signal and a direct current

voltage corresponding to a part of the power of a transmission output signal.

24. (currently amended): A The distortion compensation method as set forth in claim 19, wherein said correction data component consists of a predetermined amplitude value and a predetermined phase value of the transmission signal.